

PRODUCTS SPECIFICATIONS

LPG		
SPEC. nr: L005	DATE: 06.05.2024	REV. 10

METHOD	MAX.	MIN.	UNITS	DESCRIPTION
IP 235	0.570	0.539	----	SPEC. GRAVITY@15C
ASTM D 1267	13.8	10	bar	VAPOR PRESSURE@50C
ASTM D 1837	2	---	C	95% DISTILLATION POINT
ASTM D 2158	0.05		ml	DISTILLATION RESIDUE@37.8C
ASTM D 2420	NOT DETECTABLE		----	H2S
ASTM D 6667	100		mg/kg	SULFUR CONTENT
ASTM D 6228	150	50	mg/kg	ETHYL MERCAPTAN
ASTM D 2163 + D 3588	---	47,300	kJ/kg	HIGH HEATING VALUE
ASTM D 2163 + D 3588	---	43,900	kJ/kg	LOW HEATING VALUE
ASTM D 2163	3.2	---	mol.%	C1+C2 CONTENT
ASTM D 2163	2.0	---	mol.%	C5+ CONTENT
ASTM D 2163	0.1	---	mol.%	1,3-BUTADIENE CONTENT
ASTM D 2163	20	---	mol.%	OLEFINS CONTENT
----	NOT DETECTABLE		----	ALKALINITY (NaOH)